

INTERACT® | AT-Skype



Skype Group Conferencing Solution

NEW

Add your conferencing room to SKYPE with the INTERACT AT-Skype — a complete conference room solution with flexibility in mind. The INTERACT AT connects to the Skype PC with USB audio and includes all the necessary audio equipment and peripherals for any conference room while delivering exceptional audio quality at an affordable price.

Customize your solution with multiple microphones and speaker options, direct connection to enterprise telephones, USB audio, a room controller, plus the ability to connect to the rich-media systems and the room is ready for a Skype conference..



A USB-ENABLED AUDIO CONFERENCING SOLUTION

APPLICATIONS

- + Use Collaboration capabilities in the group room with rich-media systems
 - > Web Conferencing
 - > Personal Computer
 - > IP Telephony
 - > Video Conferencing
- + Board Rooms
- + Conference Rooms
- + Executive Offices

ADVANTAGES

- + Bring Skype into the Conference Room
 - > Just add a PC to run Skype
 - > The PC connects to INTERACT AT-Skype via USB
- + Create Group Video Conferencing using Skype at a fraction of the cost
 - > Just add the PC, LCD and Camera to the INTERACT AT-Skype
 - > HD capabilities with Skype
- + As easy to install as a Conferencing Phone
 - > Plug & Play
 - Connect the Microphones to the Mixer
 - Connect the Speakers to the Mixer
 - Connect the Dialer to the Mixer
 - Connect a PC to the USB Port
 - > No programming required
 - > Uses Desktop Skype

> COMPONENTS

Optional accessories available individually or in predefined bundles.



INTERACT AT MIXER

Provides advanced audio processing for superior sound quality.



INTERACT MIC

Each pod features two voice-activated mic elements for 360° audio pickup.



INTERACT COM (Wired or Wireless)

Provides an interface to telephone sets via the headset port or to PC audio via a USB port. The Wireless Com provides the interface to a wireless controller.



CLEARONE LOUDSPEAKERS

Ceiling or wall-mount options provide premium sound. Also available without speakers for custom speaker options.



INTERACT Dialer (Wired or Wireless)

Controller provides an intuitive interface that emulates a telephone keypad.



INTERACT MIC EX

Each box contains three industry standard XLR microphone connectors. Boxes are daisy-chained from mixer using standard RJ-45 cables. Boxes can be rack-mounted with mixer or strategically positioned throughout a room to minimize microphone cable runs.



> SPECIFICATIONS

AUDIO PERFORMANCE

Conditions: Unless otherwise specified, all measurements are performed from 20 Hz to 15 kHz BW limit (No Weighting)
Dynamic Range:
> 80 dB (Non-A Weighted) THD+N: < 0.02%

AUDIO MIXER

AEC Tail Time: 128 ms
Adaptive Noise Cancellation: 6-15 dB
Gating: Adaptive Ambient, 1st Mic Priority, Look-ahead Gating
Up to a total of 3 INTERACT MIC or INTERACT MIC EX devices can be connected to the INTERACT AT Mixer
48 kHz Sample Rate, 24-bit Resolution

AUDIO MIXER LINE INPUT

Connection: Unbalanced RCA
Impedance: 10 kΩ
Nominal Level: -10 dBu
Maximum Level: +9 dBu

AUDIO MIXER PLAYBACK

Connection: Unbalanced Left and Right RCA (Summed Internally)
Impedance: 10 kΩ
Nominal Level: -10 dBu
Maximum Level: +15 dBu

AUDIO MIXER LINE OUTPUT

Connection: Unbalanced RCA
Impedance: 10 kΩ
Nominal Level: -10 dBu
Maximum Level: +9 dBu

AUDIO MIXER RECORD OUTPUT

Connection: Unbalanced Left and Right RCA (Mono Source Split Internally)
Impedance: 10 kΩ
Nominal Level: -10 dBu
Maximum Level: +9 dBu

AUDIO MIXER AMPLIFIER OUTPUT

Connection: Left and Right Push Terminals
Power: 5 Watts
Frequency Response: 50 Hz to 15 kHz (+/-3.5 dB)
Dynamic Range:
> 80 dB
THD+N:
< 0.50% @ 1W

TELEPHONE INTERFACE

Telephone Audio Performance
Conditions: Unless otherwise specified, all measurements are performed with Transmit Limiter and Receive ALC disabled

Frequency Response:
250 Hz to 3.3 kHz ±2.5 dB THD+N: < 0.30%
re-max level 250 Hz to 3.3 kHz
SNR: > 62 dB re-max level

Telco Line Echo Cancellation

Tail Time: 32 ms
Null: 55 dB Nominal

Telephone Noise Cancellation

Noise Cancellation 6-15 dB Attenuation

RS-232 CONTROL PORT

DB9 Female
Baud Rates: 9,600 / 19,200 / 38,400 / 57,600 (Default) / 115,200
Protocol: 8 Bit / 1 Stop / No Parity
Hardware Flow Control ON (Default)/OFF

USB CONFIGURATION PORT

USB 2.0 Compatible
Type: B Connector

VISCA CAMERA PORT

Din, 9600 Baud, No Flow Control

LAN

10/100 Ethernet
RJ-45 with Activity LED
Supports: Telnet, HTTP

LINK BUS

Connection: RJ-45 with CAT5 Daisy-chained

Maximum Distance:
60 feet from Mixer to last device in chain

Maximum Number of INTERACT MIC Devices:
3 - Any Mix of INTERACT MIC or MIC EX

Maximum Number of INTERACT COM Devices:
1 per INTERACT Mixer

CONFIGURATION SOFTWARE

INTERACT Supports:
Microsoft XP Vista and Windows 7

INTERACT COM

Versions:
Wired or Wireless (2.4 GHz)

USB AUDIO CHANNEL:

USB 2.0 Compatible
Connector: Mini Type B
TX and RX Channel, 16-bit at 16 kHz

HEADSET AUDIO CHANNEL:

Connector: RJ-9

Supported Telephone Sets:

Most Cisco, Avaya, and Nortel Phones

Audio Performance

Frequency Response: 40 to 3300 Hz
THD and Noise: < 0.04% re-max level with 0 dB Gain @ 1 kHz
Dynamic Range: > 84 dB (Non A-Weighted)

Audio Processing:

Receive Automatic Level Control
Line Echo Cancellation for Side-Tone
Elimination

GPIO:

Pin 1: Global Mute (C)
Pin 2: Global Mute (S)
Pin 3: ON/OFF Hook (C)
Pin 4: ON/OFF Hook (S)
Pin 5: 5V DC up to 40 mA

INTERACT DIALER

Available in Wired or Wireless Versions

Functions: Dialing, Volume Control, Mute Control
Communications:
Wired Version: RS-232 Connected to Mixer
Wireless Version: 2.4 GHz DSSS to INTERACT COM-W (Wireless)

INTERACT MIC – TABLETOP MICROPHONE

Coverage: 360°

Frequency Response:
60 Hz - 14 kHz THD+N: < 0.08%
(-45 dBu Input @ 1 kHz)

Sensitivity: -45 dBu

INTERACT MIC EX - MICROPHONE

DISTRIBUTION BOX
Connection: Female XLR Balanced
Maximum Level: +18 dBu
Frequency Response:
20 Hz - 15 kHz THD + N: < 0.01%
Phantom Power: 24 V @ 10 mA
Impedance: 5 kΩ per Leg or 10 kΩ Balanced

POWER SUPPLY

Primary Voltage: 100 to 240 VAC
Auto-Sensing, 50-60 Hz
Power Consumption: 32 W Maximum

DIMENSIONS (W X D X H)

INTERACT AT Mixer: 17" x 7.5" x 2"
(43.2 cm x 19.1 cm x 5.1 cm)

INTERACT Dialer: 10.5" x 4.5" x 2.75"
(26.7 cm x 11.4 cm x 6.9 cm)

INTERACT MIC EX: 4.7" x 5.6" x 1.7"
(11.9 cm x 14.3 cm x 4.4 cm)

INTERACT COM: 4.7" x 5.6" x 1.7"
(11.9 cm x 14.3 cm x 4.4 cm)

INTERACT MIC: Diameter: 7" (17.8 cm)
Height: 1.5" (3.8 cm)

WEIGHT

INTERACT AT Mixer: 4.5 lbs. (2.25 kg)
INTERACT Dialer: 2.0 lbs. (1.0 kg)
INTERACT MIC: 1.5 lbs. (0.75 kg)
INTERACT MIC EX: 1.5 lbs. (0.75 kg)
INTERACT COM: 1.5 lbs. (0.75 kg)

COMPLIANCE

ROHS Compliant
WEEE Compliant
UL Safety Listed
AES48-2005 AES Standard on Grounding and EMC Practice

PART NUMBERS

Complete Room Solutions:
Call ClearOne for complete listing of room options.

INTERACT AT: 910-154-010

INTERACT COM: 910-154-030

INTERACT COM-W (For Wireless Dialer):
910-154-025

INTERACT MIC: 910-154-015

INTERACT MIC EX: 910-154-020

INTERACT Dialer: 910-154-035

INTERACT Dialer W (Wireless): 910-154-040

ClearOne Wall Speaker: 910-151-002-01

ClearOne Ceiling Speaker: 910-151-001-01

> CLEARONE LOCATIONS

HEADQUARTERS:

Salt Lake City, UT USA
5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

Tel: 801.975.7200
Toll Free: 800.945.7730
Fax: 801.977.0087
E-mail: sales@clearone.com

EMEA
Tel: 44 (0) 1189.036.053
E-mail: global@clearone.com

APAC
Tel: 801.303.3388
E-mail: global@clearone.com

LATAM
Tel: 801.974.3621
E-mail: global@clearone.com

Technical Sales
Tel: 800.705.2103
E-mail: techsales@clearone.com

Technical Support
Tel: 800.283.5936
E-mail: tech.support@clearone.com