

MAX™ IP Response Point™

Expandable VoIP Conferencing Phone for Microsoft® Response Point™ Phone Systems

The industry's first conference phone for the Microsoft® Response Point phone system, MAX IP Response Point brings high performance audio to the SMB. MAX IP Response Point contains HDConference™ audio processing technologies for unrivaled audio performance as well as the ability to daisy-chain up to four phones together, providing better room coverage and control.

ClearOne®



Microsoft®
Response Point

FLEXIBLE, HIGH
PERFORMANCE
AUDIO FOR
RESPONSE
POINT USERS

APPLICATIONS

Executive Office
Small Conference Room
Medium Conference Room
Large Conference Room
Training Room
Separate Rooms (linked phones can be separated for use in different rooms)

ADVANTAGES

Response Point Feature Set

- + Single blue button connects you to the Microsoft Response Point voice-activated phone system
- + Supports 3-way calling

Superior Audio Performance

- + High-quality full duplex sound enables participants to speak and listen at the same time without sound cutting in and out
- + Distributed Echo Cancellation® effectively eliminates echo
- + Noise cancellation removes background noises from fans, HVAC systems, lights, projectors, etc.
- + Automatic level controls keep participants' audio balanced and consistent
- + First-mic priority eliminates hollow "tunnel" sound by activating only the microphone closest to the person speaking
- + Three microphones provide 360° audio pickup

Ease of Use & Control

- + Simple plug-and-play functionality makes installation and configuration a snap
- + Field upgradeable for easy access to latest features
- + Selectable ring tones

Expandability

- + MAX IP Response Point is a single phone but can link up to four complete phones for long or u-shaped conference tables
- + Linked phones provide multiple loudspeakers, multiple microphones, and multiple dial pads for unrivaled room coverage

> SPECIFICATIONS

Call Features

Call hold
3-way calling
Mute
Redial
Configurable dial plan

Features

DHCP
DNS
SNTP
HTTP web configuration
Dynamic firmware upgrade

SIP Support

Audio codecs
G.729A/B
G.723.1
G.711
RTP/RTCP
SDP
TCP & UDP transport
SIP proxy registration

Echo Cancellation

Tail time: 128 ms x 3

Noise Cancellation

Dynamic noise cancellation

Network Connection

10/100 Ethernet
RJ-45

Keypad

Alphanumeric standard keypad

Loudspeaker

Volume: 90dBspl A weighted @ 1 ft
Bandwidth: 200 Hz–3.3 kHz

Record Output

Connector: 2.5 mm mono audio jack
Impedance: <1000 ohms
Bandwidth: 200 Hz–3.3 kHz
Dynamic range: 60 dB
THD <.01%

Certifications

FCC part 15 Class A
UL Certified

Power

Base unit:
Auto-adjusting power module;
100-240 VAC; 50/60 Hz

Environmental

Operating temperature: 32–122° F
(0–50° C)
Storage temperature: 41–158° F
(5–70° C)
Operating humidity: 15 to 80%
Storage humidity: 10 to 90%

Dimensions (W x D x H)

Phone unit: 10.5" x 10.5" x 3"
(26.7 cm x 26.7 cm x 7.6 cm)
Base unit: 4.25" x 5.5" x 2.5"
(10.8 cm x 14 cm x 6.4 cm)

Weight

Phone unit: 2.7 lb (1.2 kg)
Base unit: .6 lb (0.27 kg)
Shipping: 10 lb (4.5 kg)

Part Numbers**MAX IP Response Point**

910-158-380 (US)

Includes:

MAX IP Response Point phone unit (1)
MAX IP Response Point base unit (1)
25' keyed cable (1)
7' Ethernet cable (1)
Documentation CD






MAX IP Response Point**Expansion Kit**

910-158-391 (US)

Includes:

MAX IP phone unit (1)
12' keyed cable (1)
Documentation CD

> ROOM APPLICATIONS

MAX IP Response Point**MAX IP Response Point + 1 Expansion Kit****MAX IP Response Point + 2 Expansion Kits****MAX IP Response Point + 3 Expansion Kits**

> CLEARONE LOCATIONS

Headquarters:

Salt Lake City, UT USA
5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116
Tel: 801-975-7200
Toll Free: 800-945-7730
Fax: 801-977-0087
sales@clearone.com

Latin America

Tel: 801-974-3621
global@clearone.com

EMEA

Tel: 44 (0) 1189 036 053
global@clearone.com

APAC

Tel: 801-303-3388
global@clearone.com

Asia-Pacific Support Center

Tel: 852-3590-4526
techsupport.apac@clearone.com