

Touch Panel Controller CONVERGE[®] Pro 2



ClearOne's Touch Panel Controller, a highly intuitive 10-inch, touch-screen device designed for CONVERGE Pro 2, allows users to control their audio conference, including managing contacts and placing and controlling calls.

Flexible connectivity options and a choice of tabletop, wall, or VESA mounting options offer an integrator-friendly solution that fits perfectly in any space.

Call Management

- + On-screen dialpad
- + Make & receive PSTN / VoIP calls
- + Multi-party conference calls
- + Call control hold, transfer, forward, history

Contact Management

- + Phone book
- + Favorite contacts
- + Search contacts
- + Import/Export contacts

Control

- + Microphone Mute control
- + Speaker Volume control
- + Programmable custom control

Flexible Mounting

- + Tabletop mount
- + Wall mount
- + 3rd-party mount with VESA Standard

Touch Panel

- + 10.1" (25.7 cm) screen size
- + Capacitive touch screen
- + 1280 x 800 resolution

Connectivity & Power

- + RS232, Ethernet, Wi-Fi
- + Direct connection to CP2 and its expanders
- + Power: AC, PoE, Power over P-Link

VENUES

Boardrooms

Conference Rooms

Huddle Rooms

Training Rooms

Lecture Halls

Courtrooms

Auditoriums

Telemedicine Facilities

ClearOne.

Touch Panel Controller Top panel



Touch Panel Controller Bottom panel



PRODUCT SPECIFICATIONS

SCREEN SIZE

10.1" (25.7 cm)

MAXIMUM HD RESOLUTION 1280 X 800

VIEWING ANGLE 85 / 85 / 85 / 85

COLOR BRIGHTNESS 16.7 M

CONTRAST RATIO 500:1

BRIGHTNESS 350 cd/m2

ASPECT RATIO 16:10

RESPONSE TIME 5 ms

NETWORK PORT RJ45 Ethernet port, 10/100 Mbps

POE PORT RJ45 Ethernet port (same as Network Port)

WI-FI Built-in Wi-Fi 802.11b/g/n, antenna & dust-cap included

SERIAL PORT RS232 (male)

USB PORT For firmware upgrade

CASE Metal case (Black)

INPUT POWER

6 W

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way, Suite 500 Salt Lake City, UT 84116

US & Canada Tel: 801.975.7200 TollFree: 800.945.7730 Fax: 801.303.5711

Tel: +1.801.975.7200 global@clearone.com

Tel: 801.975.7200 sales@clearone.com TechSupport

Tel: 801.974.3760 tech.support@clearone.com

Other product names may be registered trademarks of their respective owners who do not necessarily endorse ClearOne or ClearOne's products. All rights reserved. Information in this document subject to change without notice. DST-0042-001 Rev1.0 © 2017 ClearOne.

POWER INPUT Power Adapter or PoE

MOUNTING OPTIONS VESA standard screw holes

DIMENSION 10.3 x 6.9 x 1.3 in (261 x 174 x 32 mm)

OPERATING TEMPERATURE 32 to 104 degree Fahrenheit (0 to 40 degree Celsius)

WEIGHT 2.4 lbs (1.1 kg)

PART NUMBERS

Part Number	Product
910-3200-504-50	Serial Cable – 50 Feet (15.2 m)
910-3200-504-100	Serial Cable – 100 Feet (30.5 m)
910-3200-505	Serial to Phoenix Euroblock Adapter
910-3200-202	PoE power supply kit for 3 devices
910-3200-204-50	50 ft (15.2 m) RJ45 CAT6 Cable
910-3200-204-100	100 ft (30.5 m) RJ45 CAT6 Cable
910-3200-204-150	150 ft (45.7 m) RJ45 CAT6 Cable
910-3200-204-200	200 ft (61 m) RJ45 CAT6 Cable