


# UNITE® 150 PTZ Camera



Professional-grade HD USB PTZ camera for conference rooms, webconferencing, UC applications and more.

- > Full HD 1080p30 video, 12x optical zoom, and capability to capture all participants in the room.
- > Control the camera's functions via IR remote, RS-232, or UVC protocol.
- > Super-high SNR with advanced 2D and 3D noise reduction.
- > Compatible with popular applications such as Zoom, Webex, GoToMeeting, and more.
- > Supports USB 3.0 and 2.0 interfaces.

### APPLICATIONS

- PC-Based Video Conferencing
- Web Conferencing
- Unified Communications

### WORKSPACES

- Conference Rooms
- Executive Offices
- Training Centers
- Classrooms



### Enterprise-class video

Transforms any meeting room into a professional-grade video collaboration room.



### Plug-and-play

Simple USB 3.0/2.0 compatibility with UVC and UAC protocol support.

Great Ideas Need to be Seen™

# UNITE® 150 PTZ Camera

- CAMERA** .....
- Video System
    - HD: 1080p30
    - 1080p25
    - 720p30
    - 720p25
  - Sensor: 1/2.7 inch, CMOS
  - Effective Pixel: 2.07 M
  - Scanning Mode: Progressive
  - Lens: 12x, f3.5 mm – 42.3 mm, F1.8 – F2.8
  - Focus Mode: Auto Focus
  - Minimal Illumination: 0.5 Lux @ (F1.8, AGC ON)
  - Shutter: 1/30 s – 1/10000 s
  - White Balance: Auto, Indoor, Outdoor, One Push, Manual
  - Backlight Compensation: Supported
  - Digital Noise Reduction: 2D & 3D Digital Noise Reduction
  - Video S/N: ≥55 dB
  - Horizontal Angle of View: 72.5 ° – 6.9 °
  - Vertical Angle of View: 44.8 ° – 3.9 °
  - Horizontal Rotation Range: ±170 °
  - Vertical Rotation Range: -30 ° – +90 °
  - Pan Speed Range: 1.7 ° – 100 °/s
  - Tilt Speed Range: 1.7 ° – 69.9 °/s
  - H & V Flip: Supported
  - Image Freezing: Supported
  - Number of Presets: 255
  - Flexible Installation: Standard mount, upside-down mount

- INPUT/OUTPUT INTERFACE** .....
- Audio Interface : 1 - CH 3.5 MM Audio Interface, Line In
  - USB Interface : 1 x USB 3.0: type C female jack
  - Communication :
    - 1 x RS-232 : 8 - Pin Min din, Max. Distance: 30 m, Protocols: VISCA/Pelco-D/Pelco-P
    - 1 x RS-485 : 2 - Pin Phoenix port; Max. Distance: 1200 m, Protocols: VISCA/Pelco-D/Pelco-P

- USB FEATURES** .....
- Operating Systems: Windows 7 and later
  - Color System: YUV 4:2:2
  - Video Formats
    - USB 3.0: 1080p30
    - 1080p25
    - 720p30
    - 720p25
    - USB 2.0: 720P30 maximum

**NOTE:** Due to limitations with USB 2.0, video quality would be downgraded.  
USB 2.0 extenders are not recommended.

- USB Video Communication: UVC 1.0 - UVC 1.5
- Audio on USB: Supported
- UVC PTZ: Supported

# UNITE® 150 PTZ Camera

- GENERIC SPECIFICATIONS**.....
- Power Jack: JEITA type (DC In 12 V)
  - Input Voltage: DC 12 V
  - Current Consumption: 1.0 A (max)
  - Power Consumption: 12 W (max)
  - Operating Temperature: 14 °F–104 °F (-10 °C – 40 °C)
  - Storage Temperature: -40 °F – 140 °F (-40 °C – 60 °C)
  - MTBF: >30000 h
  - Dimensions: 5.67 x 5.67 x 6.61 " (144 x 144 x 168 mm)
  - Weight: 2.0 lb (0.91 Kg)
- OPTIONAL ACCESSORIES**.....
- 910-2100-104: Wall Mount for UNITE 150 Camera
  - 910-2100-204: Ceiling Mount for UNITE 150 Camera
  - 910-2100-002: USB 3.0 Cable
- PART NUMBER** .....
- 910-2100-004

## SALES AND INQUIRIES

---

### Headquarters

5225 Wiley Post Way  
Suite 500  
Salt Lake City, UT 84116

### US & Canada

Tel: +1.801.975.7200

### International

Tel: +1.801.975.7200

### Sales

Tel: +1.801.975.7200  
sales@clearone.com

### Tech Support

Tel: +1.801.974.3760  
videotechsupport@clearone.com