

The INTERACT AT-Skype is the only room conferencing solution with built-in audio conference bridging and interoperability for video conferencing, unified communications and teleconferencing. Skype certified, the plug-and-play solution bundle includes the INTERACT AT mixer, microphone array, tabletop dialer, speakers and UC interface.



## Applications

### Multipurpose room conferencing solution

- Video Conferencing
- Unified Communication
- Teleconferencing

### Bring Skype to meeting rooms

- Boardroom
- Training Center
- Executive Office
- Conference Room

## Features

- + Skype certified; also works with other UC applications including Avaya one-X® Communicator, IBM Sametime®, Microsoft Lync™ and others
- + Compatible with video codecs including Cisco, Lifesize, Polycom, Vidyo and others
- + Audio conference bridging allows communication between Skype, telephone and H.323/SIP video conference participants at the same time
- + Telephone interface supports standard analog PSTN, as well as connection to popular enterprise phones including Avaya, Cisco, NEC and others
- + Distributed echo cancellation and automatic gating control
- + Microphone arrays can daisy-chain to support up to 9 microphones with complete 360° coverage for large conference rooms with 12-16 participants
- + Audio recording and playback
- + INTERACT dialer with intuitive interface emulates a familiar telephone keypad
- + Controllable via third-party room control systems such as AMX or Crestron
- + PTZ camera control for voice-tracking
- + Remote configuration, control and monitoring

## INTERACT AT SKYPE AND UC INTERFACE BACK PANEL



Mixer



UC Interface\*

## Functional Specifications

### AUDIO CHARACTERISTICS

#### Audio Performance

Conditions: Unless otherwise specified, all measurements are performed from 20 Hz to

15 kHz BW limit (No Weighting)  
Dynamic Range: > 80 dB (Non-A Weighted) THD+N: < 0.02%

#### Audio Mixer

AEC Tail Time: 128 ms  
Adaptive Noise Cancellation: 6-15 dB  
Gating: Adaptive Ambient, 1st Mic Priority, Look-ahead Gating  
48 kHz Sample Rate, 24-bit Resolution

### AUDIO INPUT

#### Mic Input

Up to 9 balanced microphone inputs with daisy-chainable 3 microphone arrays

#### Audio Mixer Line Input

Connection: Unbalanced RCA  
Impedance: 10 kΩ  
Nominal Level: -10 dBu  
Maximum Level: +9 dBu

#### Audio Mixer Playback Input

Connection: Unbalanced Left and Right RCA (Summed Internally)  
Impedance: 10 kΩ  
Nominal Level: -10 dBu  
Maximum Level: +15 dBu

### AUDIO OUTPUT

#### Audio Mixer Line Output

Connection: Unbalanced RCA  
Impedance: 10 kΩ  
Nominal Level: -10 dBu  
Maximum Level: +9 dBu

#### Audio Mixer Record Output

Connection: Unbalanced Left and Right RCA (Mono Source Split Internally)  
Impedance: 10 kΩ  
Nominal Level: -10 dBu  
Maximum Level: +9 dBu

#### Speaker Output

Connection: Left and Right Push Terminals  
Power: 5 Watts  
Frequency Response: 50 Hz to 15 kHz (+/- 3.5 dB)  
Dynamic Range: > 80 dB  
THD+N: < 0.50% @ 1W

### TELECONFERENCING INTERFACE

#### PSTN Telephone Line

Telephone Audio Performance  
Conditions: Unless otherwise specified, all measurements are performed with Transmit Limiter and Receive ALC disabled

#### Frequency Response:

250 Hz to 3.3 kHz ±2.5 dB THD+N: < 0.30% re-max level 250 Hz to 3.3 kHz  
SNR: > 62 dB re-max level

#### Telco Line Echo Cancellation

Tail Time: 32 ms  
Null: 55 dB Nominal

#### Telephone Noise Cancellation

Noise Cancellation 6-15 dB Attenuation

### Enterprise Phone Connection

Headset Audio Channel (UC Interface):  
Connector: RJ-9

#### Audio Performance

Frequency Response: 40 to 3300 Hz  
THD and Noise: < 0.04% re-max level with 0 dB Gain @ 1 kHz  
Dynamic Range: > 84 dB (Non A-Weighted)

#### Audio Processing:

Receive Automatic Level Control  
Line Echo Cancellation for Side-Tone Elimination

### UNIFIED COMMUNICATION INTERFACE (UCI)

#### USB Audio Channel:

USB 2.0 Connection to PC  
Connector: Mini Type B  
TX and RX Channel, 16-bit at 16 kHz

### VIDEO CODEC CONNECTION

#### Line Input/Output

RCA connection

### MANAGEMENT AND CONTROL

#### RS-232 Control Port

DB9 Female  
Baud Rates: 9,600 / 19,200 / 38,400 / 57,600 (Default) / 115,200  
Protocol: 8 Bit / 1 Stop / No Parity  
Hardware Flow Control ON (Default)/OFF

#### USB Configuration Port

USB 2.0 Compatible  
Type: B Connector

### VISCA Camera Port

Din, 9600 Baud, No Flow Control

### LAN

10/100 Ethernet  
RJ-45 with Activity LED  
Supports: Telnet, HTTP

### GPIO (INTERACT UCI):

Pin 1: Global Mute (C)  
Pin 2: Global Mute (S)  
Pin 3: ON/OFF Hook (C)  
Pin 4: ON/OFF Hook (S)  
Pin 5: 5V DC up to 40 mA

### Configuration Software

INTERACT Support:  
Microsoft XP, Vista and Windows 7

### EXPANSION INTERFACE

#### Link Bus

Connection: RJ-45 with CAT5-Daisy-Daisy-Daisy-chained

Maximum Distance:  
60 feet from Mixer to last device in chain

Maximum Number of INTERACT MIC Devices: 3 - Any Mix of INTERACT MIC or MIC EX

Maximum Number of INTERACT UCI Devices: 1 per INTERACT Mixer

### COMPONENT ACCESSORIES

#### UC Interface

USB connection to PC  
Headset connection to enterprise phones

#### INTERACT Dialer

Available in Wired or Wireless Versions  
Functions: Dialing, Volume Control, Mute Control  
Communications:  
Wired Version: RS-232 Connected to Mixer

#### INTERACT MIC

##### Tabletop Microphone Array

Coverage: 360°  
Frequency Response: 60 Hz - 14 kHz  
THD+N: < 0.08% (-45 dBu Input @ 1 kHz)  
Sensitivity: -45 dBu

#### Stereo Speakers

2 wall-mount speakers

### POWER SUPPLY

Primary Voltage: 100 to 240 VAC  
Auto-Sensing, 50-60 Hz  
Power Consumption: 32 W Maximum

### MECHANICAL

#### Dimensions (W x D x H)

INTERACT AT Mixer: 17" x 7.5" x 2"  
(43.2 cm x 19.1 cm x 5.1 cm)

INTERACT MIC: Diameter: 7" (17.8 cm)  
Height: 1.5" (3.8 cm)

INTERACT Dialer: 10.5" x 4.5" x 2.75"  
(26.7 cm x 11.4 cm x 6.9 cm)

INTERACT UCI: 4.7" x 5.6" x 1.7"  
(11.9 cm x 14.3 cm x 4.4 cm)

#### Weight

INTERACT AT Mixer: 4.5 lbs. (2.25 kg)  
INTERACT Dialer: 2.0 lbs. (1.0 kg)  
INTERACT MIC: 1.5 lbs. (0.75 kg)  
INTERACT UCI: 1.5 lbs. (0.75 kg)

AES48-2005 AES Standard on Grounding

### COMPLIANCE

ROHS Compliant  
WEEE Compliant  
UL Safety Listed  
AES48-2005 AES Standard on Grounding and EMC Practice

### PART NUMBERS

INTERACT AT-Skype Bundle: 930-154-003

\* Formerly known as COM Box

## ClearOne Contacts

### North America

Tel: 801-975-7200  
Toll Free: 800-945-7730  
Fax: 801-977-0087  
sales@clearone.com

### Europe & Oceania

Tel: +44 (0) 1189 036 053  
global@clearone.com

### Asia Pacific

Tel: +852 3590 4526  
global@clearone.com

### Latin America

Tel: 801-974-3621  
global@clearone.com

### Middle East

Tel: +852 3590 4526  
global@clearone.com