



## VoIP/SIP Network Settings Worksheet

A/V Integrators and IT managers - use this form to streamline the network setup process of ClearOne products with VoIP/SIP interfaces. The VH20 (and similar products) require the use of a standard SIP connection with any VoIP enabled system; this may require the purchase of additional software/licenses from a third party vendor.

Configuring a ClearOne VoIP enabled product requires the information asked in this worksheet. Please coordinate with the site IT manager to obtain the information prior to installation.

### Basic Settings

Phone Number: \_\_\_\_\_

Authorization User: \_\_\_\_\_

Authorization Password: \_\_\_\_\_

Will this device obtain an address from a DHCP Server? **Yes / No**

Proxy IP Address/URL: \_\_\_\_\_

**Note:** Enter the above address as the Dial Plan Domain Name/IP Address

Port: \_\_\_\_\_

Outbound Proxy IP/URL : \_\_\_\_\_

Port: \_\_\_\_\_

Listen Port: \_\_\_\_\_

VLAN Priority: \_\_\_\_\_

VLAN ID (1-4094): \_\_\_\_\_

## SIP Settings

SIP Transport Protocol (Circle applied protocol)

- UDP
- TLS
  - Private Key, Local Cert, CA Certs - Please obtain locations and files from IT administrator.
- TCP

## Dial Plan

- If a Dial Plan does not exist for the network, ask the IT administrator to provide you with the desired information to create one in the unit.

**Save your changes** in the Setup tab by clicking **OK**

For information about other setup options and settings, please refer to the user's manual for your device.