



TECHNICAL NOTE

→MAX 100

Record out specifications of the ClearOne Max phones

Introduction

This document will detail the specifications of the record output on the ClearOne Max Wireless and ClearOne Max EX conference phones.

Description

Below are the detailed specifications of the record output on the ClearOne Max EX and ClearOne Max wireless bases. This record out has been designed for use with digital voice recorders that are commonly available and has been tested with several different models.

Specifications

up an inactive (high) command.

Output level	-30 Dbu (approximately 0.6 mV into a 3k ohm load)
Connection	2.55 mm mono jack (unbalanced, 2-wires: + and ground)

This connection contains both sides of the conversation, send and receive.

Some of the recorders we tested with are as follows: Sony ICD-ST10, Sony ICD-B10, Olympus VN-3600, Olympus S711, Panasonic RR-US350

→ CLEARONE LOCATIONS

Headquarters:
Salt Lake City, UT USA
1825 Research Way
Salt Lake City, UT 84119
Tel: 801-975-7200;
800-945-7730
Fax: 801-977-0087
sales@clearone.com

Champlin, MN USA
Tel: 801-942-3776
sales@clearone.com

Latin America Offices
Tel: 801-974-3621
global@clearone.com

London, UK
Tel: 801-974-3792
global@clearone.com

Hong Kong
Tel: 801-303-3441
global@clearone.com

Singapore
Tel: 801-303-3495
global@clearone.com