

ClearOne Aura™

With **Aura**,
Professionals can
now **Re-imagine**
their **Workspaces**
at **Home**

Versa Pro 50



Includes ClearOne's CONVERGE® Huddle, audio processor, UNITE® 50 ePTZ camera and a 360-degree coverage ceiling mic array for professional audio and video in your home office.

Aura Professional Home Office Solution

Dramatically enhances the audio and video experience for any **cloud-based video collaboration** application for your **professional home office**




Highlights

- ✦ CONVERGE® Huddle audio processor for a professional audio experience.
- ✦ Ceiling Microphone Array with 360-degree coverage reducing noise and reverberation.
- ✦ UNITE® 50 4K ultra-wide 120-degree ePTZ camera with 1080p30, and 3x digital zoom for high video quality no matter where the camera is installed in your home office.
- ✦ Configure Versa Pro CT directly through the USB port, or use network Ethernet jack.
- ✦ Add pro-quality audio and 4K video to your app, such as COLLABORATE® Space, Microsoft® Teams, WebEx™, Zoom™, Google® Meet™, and more.
- ✦ FREE COLLABORATE® Space lifetime subscription — ClearOne's high quality award-winning cloud-based video collaboration application.
- ✦ Add the Bluetooth Wall Panel to make this system smart speaker ready. Supports Alexa, Cortana, Google Home, and Siri.

Aura Professional Home Office Application

Complete your **Versa Pro 50** setup by adding other ClearOne Aura products



* Small enough to easily mount behind the room display

Specifications

+ AUR-3200-050 Versa Pro 50

INCLUDES

- + AUR-3200-701 CONVERGE® Huddle
- + AUR-2100-004 UNITE® 50 4K ePTZ camera
- + AUR-001-013-W Ceiling Mic Array (White)
- + AUR-3200-202 PoE Injector Kit
- + Free COLLABORATE® Space lifetime subscription

CONVERGE HUDDLE

- + INPUT/OUTPUT INTERFACE
 - INPUTS
 - 3-channel balanced mic/line inputs with AEC
 - 1 channel balanced line input without AEC
 - 3.81mm orange-color Phoenix/Euroblock type push-on mini-terminal block
 - LINE OUTPUTS
 - 2-channel balanced line outputs, 3.81 mm black-color Phoenix/Euroblock type, push-on mini-terminal block
 - USB CONNECTIONS
 - 1 USB 3.0 Type-B
 - 1 USB 3.0 Type-A
 - RJ-45, 10/100/1000Mbps, passthrough to USB-B 3.0
- + VIDEO FORMATS
 - 1600 x 1200p @ 60Hz, 4:3 ratio
 - 1920 x 1200p @ 60Hz, 16:10 ratio
 - 2560 x 1440p @ 60Hz, 16:9 ratio
- + ENVIRONMENTAL
 - Thermal: 116 BTU/Hr Typical
 - Operating Temperature: 14° F to 104° F (-10° C to 40° C) Ambient Temperature
- + AMPLIFIER OUTPUT
 - Type: 5.08 mm Black Phoenix type, Euroblock
 - Audio: 2 Channels
 - Output Power: 10 W Max, 8Ω load
 - Frequency Response: 20 Hz – 22 kHz @ 10 dBu, +/- 0.5 dBu

- THD + N (Total Harmonic Distortion + Noise): 20 Hz – 22 kHz @ 10 dBu, 1 W, <0.3%
- Dynamic Range: 20 Hz – 22 kHz @ 20 dB, >102 dB with 20 kHz digital low pass filter
- Crosstalk (Mic/Line): Channel-to-channel, stimulus at 20 dBu to receptor, < -70 dB

CEILING MICROPHONE ARRAY

- + ACOUSTIC CHARACTERISTICS
 - Polar Pattern: Cardioid
 - Dynamic Range: 80 dB, 1 kHz @ max SPL
 - Signal/Noise Ratio: 60 dBA, 1 kHz @ 1Pa
 - Frequency Response: 100 Hz - 12 kHz
 - Sensitivity: 114 mV/Pa
- + ELECTRICAL CHARACTERISTICS
 - Element: Fixed-charge back plate permanently polarized condenser
 - Phantom Power Requirement: 12-52 vdc, 2 mA typical
 - Impedance: 200 Ω

UNITE 50 4K ePTZ CAMERA

- + VIDEO FORMATS: 4K30, 1080p30, 1080p25, 720p30, 720p25, 960x540p30, 960x540p25, 640x360p30, 640x360p25, etc.
- + 4K: down-compatible with 1080p30 and 720p
- + Sensor: 1/2.5", CMOS, Effective pixel: 8.29M
- + Scanning mode: Progressive
- + Lens: Focus: f=2.8 mm, FOV: 120°
- + Minimal illumination: 0.05 Lux @ (F1.8, AGC ON Shutter: 1/30 s – 1/10000 s
- + White balance: auto, indoor, outdoor, one-push, manual
- + Backlight compensation: Supported
- + Digital Noise Reduction: 2D & 3D
- + Horizontal angle of view: Wide angle up to 120°
- + Electronic Pan Tilt Zoom
- + Installation: Equipped with damping rotary shaft bracket to fit almost any display

Specifications

✦ AUDIO

- Built-in microphone array on configuration

✦ COMPATIBILITY

- Operating Systems: Windows 7, Windows 8, Windows 8.1, Windows 10, Mac OS, Linux
- USB video communication: UVC 1.0/1.1
- UVC PTZ: Supported

✦ INPUT/OUTPUT INTERFACE

- USB interface: 1xUSB 3.0: Type B, female

✦ POWER

- Input voltage: 5v (USB power supply)
- Current consumption: 600 mA
- Power consumption: 3.0 W

✦ ENVIRONMENTAL

- Operating temperature: 14° F ~ 104° F (-10° C ~ 40° C)
- Storage temperature: -40° F ~ 140° F (-40° C ~ 60° C)
- MTBF: >30000h

✦ MECHANICAL

- Dimensions (W x D x H): 7.64 x 1.34 x 1.65”
(194 x 34 x 42 mm) (without bracket)
- Weight: 0.74 lb (0.34 kg)

OPTIONAL CLEARONE PERIPHERALS

- ✦ AUR-3200-303 Bluetooth Wall Panel
- ✦ AUR-151-010-B Passive Wall Speakers
- ✦ AUR-3200-204-50 RJ45 CAT6 Cable – 50’
- ✦ 910-3200-702-30 USB 3.0 Cable – 33’
- ✦ 693-153-050 Speaker Cable – 50’

Sales & Inquiries

Headquarters

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

Headquarters

US: +1.801.975.7200
International: +1.801.975.7200

Aura Sales

US: +1.888.HEY.AURA
International: +1.801.975.7200
aurasales@clearone.com

Aura Tech Support

US: +1.888.HEY.AURA
International: +1.801.975.7200
auratechsupport@clearone.com