

## RELEASE NOTES

### CONSOLE® AI Lite Software and Firmware

**PRODUCTS SUPPORTED:**  
COLLABORATE® Versa Lite CT  
COLLABORATE® Versa Room CT

July 2, 2021

### RELEASE 07.02.2021

#### CONSOLE AI Lite v1.1.6.0

1. Faster firmware upgrade

#### COLLABORATE Versa USB v1.0.3.6

1. Fixed issue where a factory default was sometimes required out of the box
2. Fixed rare issue with USB name sometimes showing strange characters
3. Fixed issue with PoE port LED not correctly showing status
4. Fixed issue with BMA CTH speaker output levels not being correctly initialized after a factory default

#### Known Issues

1. Performing the firmware upgrade will restore factory defaults on the Versa USB and will cause all custom settings to be lost. If you want to preserve your settings, save the project file to your hard drive first, perform the firmware upgrade, and then restore the project file.

### RELEASE 11.10.2020

#### CONSOLE AI Lite v1.1.5.0

#### COLLABORATE Versa USB v1.0.2.0

#### BMA CTH v1.1.0.15

#### Bluetooth Expander v1.0.1.18

#### New

1. Added Undo/Redo in CONSOLE AI Lite

2. New default values for beam audio to better match most rooms: NC = Enabled @ 6 dB, HPF @ 80 Hz, LPF @ 5.4 kHz
3. Added an always-on limiter to the speaker outputs to prevent brown outs when loud audio is played
4. Fixed connection status when Versa USB is unplugged
5. USB Rx/TX and BT Tx values are set properly when loading a file
6. Fixed CONSOLE AI Lite starting off-screen if external monitor is disconnected
7. Various bug fixes

## RELEASE 06.02.2020

### Initial Product Release

#### CONSOLE AI Lite v1.0.15.0

#### COLLABORATE Versa USB v1.0.1.34

#### BMA CTH v1.1.0.8

#### Bluetooth Expander v1.0.1.18

### Known Issues

1. The LED on the PoE Input port on the Versa USB does not light up when you apply power. Instead, to check for power, look at the Power LED on the front panel.
2. If, while connected, you unplug the Versa USB device, the connection icon in CONSOLE AI Lite appears as though you can connect again. If you click the icon, you receive a connection error.
3. If you unplug the BMA CTH or the Bluetooth Expander from the Versa USB, CONSOLE AI Lite continues to display the firmware version and the serial number, even though they are not connected.
4. The BMA CTH Mic mute mirrors the status of the microphone mute on the computer. This means if the microphone is muted in the conferencing software, then the BMA CTH Mic is also muted. However, mute sync does not work in the opposite direction--muting the BMA CTH Mic does not mute the conferencing software.
5. Polarity in the Speaker channels is not reset to off when the "Restore Factory Defaults" button is pressed.
6. The Disable Bluetooth property may not be set correctly on the device when you load a project with the property disabled. The property may be changed while connected with Console AI Lite or by pressing the button on the Bluetooth device.

---

## SALES AND INQUIRIES

### Headquarters

5225 Wiley Post Way Suite 500  
Salt Lake City, UT 84116

### Headquarters

Main: +1.801.975.7200

### Sales

Tel: +1.801.975.7200  
[sales@clearone.com](mailto:sales@clearone.com)

### Tech Support

Tel: +1.801.974.3760  
[audiotechsupport@clearone.com](mailto:audiotechsupport@clearone.com)

Product names and logos may be registered trademarks of their respective owners who do not necessarily endorse ClearOne or ClearOne's products. All rights reserved. Information in this document subject to change without notice.