

ClearOne® Aura™

With Aura,
Professionals can
now Re-imagine
their Workspaces
at Home

Versa® Pro CT



An unbeatable product offering that includes a Huddle CTH audio processor and the new Huddle-compatible and patented Beamforming Ceiling Microphone Array that is a perfect fit for a professional home office.

Aura Professional Home Office Solution

Dramatically enhances the audio and video experience for any **cloud-based collaboration** application for your **professional home office**

COMPATIBLE WITH




Enhance Your Cloud Collaboration

Highlights

- ✦ Great room solution for a professional home office using any cloud-based collaboration service such as COLLABORATE® Space, Microsoft® Teams, WebEx™, Zoom™, Google® Meet™, and more.
- ✦ Beamforming Ceiling Microphone Array with built-in AEC provides impeccable room coverage using adaptive steering (think of it as smart switching).
- ✦ 24-in or 600mm microphone array with a variety of mounting options.
- ✦ Includes mic/line inputs with AEC, line outputs, USB audio, HDMI, and 4x10 Watt power amps to drive passive wall speakers.
- ✦ Comes preloaded with a project file ready for the most common room configuration.
- ✦ Configure using CONSOLE® AI software's enhanced visualization and audio intelligence.
- ✦ Now, configure Versa Pro CT directly through the USB port, or use network Ethernet jack.
- ✦ FREE COLLABORATE® Space lifetime subscription — ClearOne's high quality, award winning cloud-based video collaboration application.
- ✦ With a rich mix of video and audio options, the Versa Pro CT is versatile, flexible, and easy to install.
- ✦ No system in the market today can compete with the Versa Pro CT on price, features, coverage, and quality experience for any cloud-collaboration application.

Aura Professional Home Office Application

Complete your **Versa Pro CT** setup by adding other ClearOne Aura products



Specifications

- ✦ AUR-3200-030-U Versa® Pro CT
- ✦ AUR-3200-030-I Versa® Pro CT Intl

INCLUDES

- ✦ 24 in (North America):
 - 910-3200-206-U BMA CTH 24 in
 - 910-3200-210 BMA Surface-Mount Kit 24 in
- ✦ 600 mm (International):
 - 910-3200-206-I BMA CTH 600 mm
 - 910-3200-210-I BMA Surface-Mount Kit 600 mm
- ✦ AUR-3200-706 CONVERGE® Huddle CTH
- ✦ AUR-3200-202 PoE Injector Kit
- ✦ Free COLLABORATE® Space lifetime subscription

BMA CTH

- ✦ Number of Beams: Two patterns, either 5 or 6 beams
- ✦ Polar Pattern: Custom
- ✦ Frequency Response: 150 Hz – 16 kHz, +/- 3 dB
- ✦ Dynamic Range: 150 Hz – 16 kHz, > 70 dB
- ✦ AMPLIFIER OUTPUT
 - Type: 5.08 mm black header, Phoenix type Euroblock
 - Audio: 2 channels
 - Output Power: 2x10 W Max, 8Ω load*
 - Frequency Response: 20 Hz – 22 kHz @ +10 dBu, +/- 0.5 dB
 - THD + Noise: 20 Hz – 22 kHz @ +10d Bu, 1 W, < 0.2%
 - Dynamic Range: 20 Hz – 22 kHz @ +20 dB, > 102 dB, with 20 kHz digital low pass filter
 - Crosstalk: Channel to Channel, stimulus at +20 dBu receptor 10W output 8Ω load, 20 Hz – 22 kHz, < -60 dB
- ✦ LED
 - 4 LED indicators on one end of unit:
 - Mute/Un-mute configuration with 8 color options, two blink patterns and warning indications
- ✦ CONFIGURATION
 - Beam enable/disable
 - Acoustic Echo Cancellation (AEC) on/off
 - Noise Cancellation (NC) on/off
 - Filters: All Pass, Low Pass, High Pass, Notch, PEQ
 - Automatic Level Control (ALC) on/off
 - Gain adjust
 - Mute on/off
 - Auto gate/Manual gate

- ✦ P-LINK PERIPHERAL BUS
 - Ports labeled as “Expander” on Huddle Chassis, and “P-Link” on BMA CTH
 - P-Link In & Out: Proprietary Network
 - Port Type: RJ-45
 - Cable: RJ45, Cat6
 - Distance: Up to 200’
- ✦ POWER SELECTION SWITCH
 - Type: Slide switch
 - Toggle towards P-Link to power device by P-Link
 - Toggle towards PoE to power device by PoE Injector
- ✦ CONFIGURATION & ADMINISTRATION SOFTWARE
 - CONSOLE AI software
 - CONVERGENCE™ AV Network Configuration software
- ✦ MOUNTING
 - Ceiling mount (24” or 600mm)
- ✦ POWER
 - Power Source: PoE Injector or equivalent
 - PoE: IEEE 802.3at compliant devices providing 56V and 640 mA (36 W)
 - P-Link In - Mode B
 - PoE In - Mode A and Mode B
 - Power Consumption:
 - 100-240VAC, 50/60Hz
 - 9.1 Watt typical without speaker amp
 - 38W at max power 1kHz (2 x 10W)
- ✦ ENVIRONMENTAL
 - Thermal: 130 BTU/Hr at max power
 - Operating Temperature: 14Â° F/-10Â° C to 104Â° F/40Â° C ambient temperature
- ✦ MECHANICAL
 - Dimensions (W x D x H):
 - 24” BMA CTH: 23.72 x 23.72 x 2.13” (602.5 x 602.5 x 54.1mm)
 - 600mm BMA CTH: 23.33 x 23.33 x 2.13” (592.5 x 592.5 x 54.1mm)
 - Weight : 7.7lb (3.5kg)

*BMA CTH requires its own PoE (IEEE 802.3 at compliant) if 2x10 W speakers are driven

Specifications

CONVERGE® HUDDLE CTH

✦ INPUT/OUTPUT INTERFACE

- INPUTS

- 3-channel balanced mic/line inputs with AEC
- 1 channel balanced line input without AEC
- 3.81 mm orange-color Phoenix/Euroblock type push-on mini-terminal block

- LINE OUTPUTS

- 2-channel balanced line outputs, 3.81 mm black-color Phoenix/Euroblock type, push-on mini-terminal block

- USB CONNECTIONS

- 1 USB 3.0 Type-B
- 1 USB 3.0 Type-A
- RJ-45, 10/100/1000Mbps, passthrough to USB-B 3.0

✦ VIDEO FORMATS

- Ultra-high resolution support (up to 2560x1600)

✦ ENVIRONMENTAL

- Thermal: 116 BTU/Hr Typical
- Operating Temperature: 14° F to 104° F (-10° C to 40° C) Ambient Temperature

✦ AMPLIFIER OUTPUT

- Type: 5.08 mm Black Phoenix type, Euroblock
- Audio: 2 Channels
- Output Power: 10W Max, 8Ω load
- Frequency Response: 20 Hz – 22 kHz @ 10 dBu, +/- 0.5 dBu

- THD + N (Total Harmonic Distortion + Noise): 20Hz – 22kHz @ 10dBu, 1W, <0.3%

- Dynamic Range: 20 Hz - 22 kHz @ +20 dBu input, > 102 dB
- Crosstalk (Mic/Line): Channel-to-Channel, stimulus at 20 dBu to receptor, < -70 dB

✦ MECHANICAL

- Dimensions (WxHxD): 7.52 x 7.83 x 1.73" (191 x 199 x 44 mm)
- Unit Weight: 2.9 lb (1.32 kg)

OPTIONAL CLEARONE PERIPHERALS

- ✦ AUR-3200-303 Bluetooth Wall Panel
- ✦ 910-3200-305 Versa USB
- ✦ AUR-151-010-B Passive Wall Speakers
- ✦ AUR-3200-204-50 RJ45 CAT6 Cable – 50'
- ✦ 910-3200-702-30 USB 3.0 Cable – 33'
- ✦ 693-153-050 Speaker Cable – 50'

Sales & Inquiries

Headquarters

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

Headquarters

US: +1.801.975.7200
International: +1.801.975.7200

Aura Sales

US: +1.888.HEY.AURA
International: +1.801.975.7200
aurasales@clearone.com

Aura Tech Support

US: +1.888.HEY.AURA
International: +1.801.975.7200
auratechsupport@clearone.com