

COLLABORATE® Live 600



COLLABORATE® Live solutions are the most versatile video collaboration room systems of their kind in the market. COLLABORATE Live 600 is a complete video collaboration system that delivers crystal-clear full duplex audio and high-quality video, perfect for mid-sized meeting rooms.

- > Two CHAT 150 speakerphones that daisy-chain to provide crystal-clear audio clarity.
- > One UNITE® 260 Pro 4K Ultra HD Camera with 20X optical zoom to capture all participants in the room.
- > User interface as intuitive and simple as familiar mobile or tablet devices.
- > Monitor, control, and audit Versa Pro CT with CONVERGENCE™ unified AV network management software



Better Together

Includes two CHAT 150 speakerphones that daisy-chain to provide crystal-clear audio clarity.



Easy to Use

User interface is as intuitive and simple as that of familiar tablets and mobile devices.

APPLICATIONS

- Video conferencing
- Audio conferencing
- Cloud video collaboration
- Wireless presentation
- Whiteboard
- Recording and streaming

WORKSPACES

- Boardrooms
- Conference rooms

Great Ideas Need to Be Seen - and Heard!™

COLLABORATE[®] Live 600

PART NUMBER	• 930-3001-602
COLLABORATE LIVE 600	<ul style="list-style-type: none">• COLLABORATE Live 600 codec appliance• UNITE 260 PTZ HD camera• CHATAttach 150 speakerphone solution• Power supplies, cables and accessories• 4-way SIP/H.323 MCU license, upgradable to 9-way• Wireless presentation licenses (1-User) , upgradable to 6-users.
COLLABORATE LIVE 600 CODEC APPLIANCE	<ul style="list-style-type: none">• Video inputs: 2 x HDMI (SIP/H.323), 2x USB• Video outputs: 1 x HDMI, 1x Display port• Audio inputs: Balanced audio, USB, Line in• Audio outputs: Balanced audio, Line out, HDMI• Dimensions: 17 x 8 x 2 ½ "(L x W x H)
UNITE 260 PRO CAMERA	<ul style="list-style-type: none">• 20X Optical zoom• Horizontal Angle of View: 60.7° – 3.36°• Vertical Angle of View: 34.1° – 1.89°• Ultra HD 4K Camera• Pan Speed Range: 1.7° – 100°/S• Tilt Speed Range: 1.7° – 69.9°/S
CHAT ATTACH 150 SPEAKERPHONE ..	<ul style="list-style-type: none">• Group USB speakerphone powered by ClearOne HDConference™ audio processing• Daisy-chainable design can expand up to two complete speakerphones to cover medium-sized rooms• Three built-in microphone array with 360° pickup• Large loudspeaker with Max Output Level: 85 dB SPL @ 1 meter• Wideband audio frequency response (20 Hz-20 kHz)
VIDEO CHARACTERISTICS	<ul style="list-style-type: none">• Resolution up to 2160P @ 30 fps• H.261, H.263, H.263+/++• H.264/AVC High Profile – up to 6 Mbps
AUDIO STANDARDS	<ul style="list-style-type: none">• 20 KHz: AAC-LD• 14 KHz: G.722.1 Annex C• 7 KHz: G.722, G.722.1• 3.4 KHz: G.711, G.723.1, G.728, G.729, AMR (3G)
DATA CHARACTERISTICS	<ul style="list-style-type: none">• H.239 support for data sharing• Resolution up to 1080p• Data inputs via HDMI, Wireless, USB
RECORDING	<ul style="list-style-type: none">• Formats: MP4, WMV• Storage options: Local, external, network (NAS)

COLLABORATE® Live 600

- STREAMING**
- Format: RTSP – Unicast and multicast streaming
 - Max number of viewers (unicast): 20
 - Max number of viewers (multicast): Depends on network
- CONTROL**
- Remote control
 - Web-based management and control
 - Telnet API for 3rd-party control
 - AMX and Crestron modules

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

US & Canada

Tel: +1.801.975.7200

International

Tel: +1.801.975.7200

Sales

Tel: +1.801.975.7200
sales@clearone.com

Tech Support

Tel: +1.801.974.3760
videotechsupport@clearone.com