ClearOne

PROFESSIONAL CAMERAS

VISUAL COLLABORATION

UNITE® 20 Pro Webcam



Pro Webcam with 85° ultra wide-angle field-of-view for use on your PC or laptop display to provide a full 1080p30 image.



Enjoy superior desktop camera quality Easily mounts on your PC or laptop display to provide a full 1080p30 image with an ultra wide-angle field-of-view.

- > Supports up to 1080p@30 Full HD.
- > 85° ultra wide-angle field-of-view.
- > Full-featured USB 2.0 interface, power supply, 2-channel USB video
- > Super-high SNR with advanced 2D and 3D noise reduction
- > Easily mounted on PC or laptop display
- > Use with PC or laptop and web conferencing applications such as Microsoft® Teams, Zoom™, WebEx™, GoToMeeting™, and others.
- > Pair the new UNITE 20 Pro Webcam with a ClearOne CHAT 50 or CHAT 150 speakerphone for the ultimate personal collaboration workspace for both highquality video and audio.



Unmatched for desktop collaboration Use with PC or laptop and webconferencing applications such as Microsoft® Teams, Zoom™, WebEx™, GoToMeeting™, and others.

APPLICATIONS

- BYOM
- Video Conferencing BYOM
- Audio Conferencing

WORKSPACES

- Small to mid-sized meeting rooms
- Boardrooms
- Executive Offices
- In-Room Presentation
 Classrooms

Great Ideas Need to be Seen[®]



UNITE® 20 Pro Webcam

VIDEO SYSTEM

VIDEO INPUTS	 1080P Full HD Sensor: 1/2.7 ", CMOS, Effective Pixel: 2.07 M Scanning Mode: Progressive Lens: Focus: f=2.8 mm, FOV: 85° Minimal Illumination: 0.05 Lux @ (F1.8, AGC ON) Shutter: 1/30s - 1/10000s White Balance: Auto, Indoor, Outdoor, One Push, Manual Backlight Compensation: Supported Digital Noise Reduction: 2D & 3D Digital Noise Reduction Horizontal Angle of View: Wide angle up to 85° Easy Installation: Equipped with damped rotary shaft bracket to fit almost any display, easy to install, stable and reliable.
AUDIO	• Built-in microphone array
USB FEATURES	 Operating Systems Windows® 7 (1080p and under only), Windows 8.1, Windows 10 or higher, Linux macOS™ 10.10 or higher, Google™ Chromebook™ Version 29.0.1547.70 or higher, 2.4 GHz Intel® Core 2 Duo processor or higher, 2 GB RAM or more, USB 2.0 port Color System /Compression: H.265 / H.264 / MJPEG Video Format: 1080p@30fps/25fps, 720p30/25, 960 x 540p30/25, 640 x 360p30/25 USB Video Communication Protocol: UVC 1.0 ~ UVC 1.5 (Optional)
INPUT/OUTPUT INTERFACE	• USB Interface: 1 x USB 2.0: Type A
GENERIC SPECIFICATIONS	 Input Voltage: 5 V (USB power supply) Operating Temperature: 14 °F ~ 104 °F (0°C ~ 40°C) Storage Temperature: -40 °F ~ 140 °F (-40°C ~ 60°C) Weight: 0.093 kg (Without bracket) 0.2 kg (with bracket) Dimensions: 4.65 x 1.46 x 1.21 " (118 x 37.2 x 30.8 mm) Bart Number: 910-2100-020

• Part Number: 910-2100-020



Scan this Code, to learn more

SALES AND INQUIRIES _

Headquarters	US & Canada	International	Sales	Tech Support
5225 Wiley Post Way Suite 500 Salt Lake City, UT 84116	Tel: +1.801.975.7200	Tel: +1.801.975.7200	Tel: +1.801.975.7200 sales@clearone.com	Tel: +1.801.974.3760 videotechsupport@clearone.com

Other product names and logos may be registered trademarks of their respective owners who do not necessarily endorse ClearOne or ClearOne's products. All rights reserved. Information in this document subject to change without notice. DST-0138-001 | V15-11022025 | ©2025ClearOne.