


COLLABORATE® Versa™ Room CT



COLLABORATE Versa Room CT provides all of the equipment and accessories needed for exceptional meeting room cloud-based video conferencing with no external DSP needed – just connect it to a computer and displays.

- > USB audio-enabled Beamforming Ceiling Tile microphone (BMA CT) brings cost-effective professional conferencing audio to small-and mid-sized meeting rooms. Built-in AEC, noise cancellation, and adaptive steering (think of it as smart switching), provides impeccable room coverage.
- > Provides a convenient single USB cable connection to the laptop or room computer.
- > UNITE 60 4K camera provides a 120-degree wide-angle field of view.
- > 2x10 Watt power amps drive the included 8-inch ceiling speakers.
- > Includes 50 ' CAT 6 cable, 30 ' USB extender cable, PoE kit, ceiling speakers, and 50 feet of speaker cable.
- > Easily and quickly configure the system using CONSOLE® AI Lite software with Audio Intelligence™ and Auto Connect™.
- > Add ClearOne's CONVERGE® Wall-Mount Bluetooth Expander to enable mobile devices to join the conference wirelessly.
- > ClearOne's BMA technology is protected by at least a dozen patents and pending patent applications.



Enhance Cloud-Based Collaboration

Delivering unbeatable price, versatility, and coverage, the Versa Room CT dramatically enhances the room audio and video experience for any cloud-based collaboration application.



Pro Audio in Smaller Spaces

USB audio-enabled Beamforming Ceiling Tile microphone brings cost-effective professional conferencing audio to small and mid-sized meeting rooms.

APPLICATIONS

- Video Conferencing
- Audio Conferencing
- In-Room Presentation

WORKSPACES


- Executive Offices
- Small to mid-sized meeting rooms
- Boardrooms

Great Ideas Need to Be Seen - and Heard!™

COLLABORATE® Versa™ Room CT

COLLABORATE Versa Room CT provides all of the equipment and accessories needed for room cloud-based conferencing with no DSP mixer needed – just connect it to a computer and displays. Add ClearOne's Wall-Mount Bluetooth Expander to enable mobile devices to join the conference wirelessly.

COLLABORATE Versa Room CT using room PC and 2 room displays, with optional ClearOne Wall-Mount Bluetooth Expander



COLLABORATE® Versa™ Room CT

INCLUDES	• CHOICE OF BMA CT - BMA CT 24 in - BMA CT 600 mm • COLLABORATE® Versa Hub • COLLABORATE® Versa USB • UNITE® 60 4K Camera • Ceiling Loudspeakers • PoE power supply kit • RJ-45 CAT 6 Cable – 50 ' • USB 3.0 Cable – 30 ' • Speaker Cable – 50 '
BMA CT	• 24 MICROPHONES - Number of Beams: Two patterns, either 5 or 6 beams - Polar Pattern: Custom - Frequency Response: 150 Hz – 16 kHz, +/- 3dB - Dynamic Range: 150 Hz – 16 kHz, > 70 dB • AMPLIFIER OUTPUT - Type: 5.08 mm Black Header, Male, Phoenix type Euroblock - Audio: 2 channels - Output Power: 2x10 W Max, 8 Ω load - Frequency Response: 20 Hz – 22 kHz @ +10 dBu, +/- 0.5 dB
CONFIGURATION	• Acoustic Echo Cancellation (AEC) on/off • Noise Cancellation (NC) on/off • Automatic Level Control (ALC) on/off • Gain adjust • Mute on/off
POWER SELECTION SWITCH	• Type: Slide Switch
CONFIGURATION & ADMINISTRATION SOFTWARE	• CONSOLE® AI Room Software
MOUNTING	• Ceiling mount (24 " or 600 mm drop-ceiling grid)
DIMENSIONS & WEIGHT	• 24 " BMA CT - 23.7 x 23.7 x 2.1 " (602.5 x 602.5 x 54.1 mm) • 600 mm BMA CT - 23.3 x 23.3 x 2.1 " (592.5 x 592.5 x 54.1 mm) • Unit Weight: 7.7 lbs (3.5 Kg)
COLLABORATE® VERSA HUB	• 1 x USB 3.0 (Type-B) for laptop (Requires Display Link driver on laptop) • 2 x USB 3.0 (Type-A) for UNITE camera & CHAT Speakerphone • 4 x USB 2.0 ports • 1 x HDMI out • 1 x DVI out
COLLABORATE® VERSA USB	• Port Type: USB-B Connector • Audio: Digital audio, 2 x 2 bidirectional channels • Sample Rate: 48 kHz • Sample Bit Depth: 24 Bit • Compatible: USB 2.0, USB 3.0 • USB Cable Distance: 16 feet (5 meters) • Compatible: Windows & Mac OS devices

COLLABORATE® Versa™ Room CT

P-LINK PERIPHERAL BUS	• Ports Type: RJ-45 (Cat 5e or Cat 6) • P-Link In & Out: Proprietary Peripheral Bus • PoE In: - P-Link In Port - PoE 802.3 af Mode B, Midspan - Power on "spare pairs" 4, 5 and 7, 8 • Cable: Solid core 24 AWG, factory terminated Cat 5e or Cat 6 cable • Distance: Up to 200 feet (60 meters)
POWER SELECTION SWITCH	• Sensor Type: Slide Switch • Toggle toward P-Link to power device by P-Link • Toggle toward PoE to power device by PoE Injector
PoE In PORT	• Port Type: RJ-45 port • PoE: 802.3 af or 802.3 at PoE/PoE+ injector input
MOUNTING	• Rack-shelf Mount, Under-Table Mount, Wall Mount, Ceiling Mount
DIMENSION & WEIGHT	• Width x Depth x Height: • Without rack-ears: - 5.5 x 1.6 x 4.1 " (139.7 x 40.6 x 104.4 mm) • With rack-ears: - 6.8 x 1.7 x 4.1 " (172.7 x 43.1 x 104.4 mm) • Unit Weight: 0.88 lbs (0.4 Kg)
UNITE® 60 4K CAMERA	• 4K 30fps, 8.29 M Pixel resolution • Smart Face Tracking, Voice Tracking • 120 ° Wide-angle Field View • Control of camera functions via IR remote control or UVC protocol • 3x Digital Zoom, f/1.8 to 2.8 Aperture
CEILING LOUDSPEAKERS	• Speaker Type: 2-way, ceiling speaker with metal back can • Frequency Range: 65 Hz to 20 kHz • Power Handling: 60 Watts RMS, 120 Watts Peak • Nominal Sensitivity: • 88 dB, 1 W @ 1m • Nominal Impedance: • 8 Ohms • Transformer Taps: - 70 V – 30 W, 15 W, 7.5 W, 3.8 W, 1.9 W - 100 V – Null, 30 W, 15 W, 7.5 W, 3.8 W • Woofer: 6.5 " (165 mm) poly-propylene cone with moisture-resistant coating • Tweeter: ¾" (19 mm) silk dome • Overload Protection: Full range power limiter with the 8 ohm direct input only, protecting the tweeter, woofer and crossover • Dimensions: 10.2 " (259.1 mm) diameter, 7.4 " (187.9 mm) deep • Net Weight (each): 7.7 lbs (3.5 Kg)

COLLABORATE® Versa™ Room CT

- SYSTEM POWER & THERMAL**
- Power Type: PoE/PoE+
 - Port Type: RJ-45
 - PoE In/P-Link In: 802.3 af or 802.3 at PoE/PoE+
 - Power Source: PoE Injector or equivalent
 - PoE: IEEE 802.3 at compliant devices providing 56 V and 640 mA (36 W).
 - P-Link In - Mode B
 - Power Consumption:
 - 100-240 VAC, 50/60 Hz, 3 Watts Typical
 - 38 W at max power 1 kHz (2 x 10 W)
 - Thermal: 130 BTU/Hr at max power
 - Operating Temperature: 14° F/-10 °C to 104 °F/40 ° C ambient temperature

- PART NUMBERS**
- INCLUDES**
- 930-3200-020-U - COLLABORATE® Versa Room CT
 - 910-3200-205-U BMA CT 24 in
 - 910-3001-100 COLLABORATE® Versa Hub
 - 910-3200-305 COLLABORATE® Versa USB
 - 910-2100-009 UNITE® 60 4K Camera
 - 910-151-001-01 Ceiling Loudspeakers
 - 910-3200-202 PoE power supply kit
 - 910-3200-204-50 RJ-45 CAT 6 Cable – 50 ‘
 - 910-3200-702-30 USB 3.0 Cable – 30 ‘
 - 693-153-050 Speaker Cable – 50 ‘
 - 930-3200-020-I - COLLABORATE Versa Room CT INTL

- INCLUDES**
- 910-3200-205-I BMA CT 600 mm
 - 910-3001-100 COLLABORATE® Versa Hub
 - 910-3200-305 COLLABORATE® Versa USB
 - 910-2100-009 UNITE® 60 4K Camera
 - 910-151-001-01 Ceiling Loudspeakers
 - 910-3200-202 PoE power supply kit
 - 910-3200-204-50 RJ-45 CAT 6 Cable – 50 ‘
 - 910-3200-702-30 USB 3.0 Cable – 30 ‘
 - 693-153-050 Speaker Cable – 50 ‘

- OPTIONAL CLEARONE PERIPHERALS** ..
- CONVERGE Wall-Mount Bluetooth Expander

- MOUNTS FOR NON-TILE CEILINGS**
- 910-3200-210 BMA Surface-Mount Kits 24 in
 - 910-3200-210-I BMA Surface-Mount Kits 600 mm
 - 910-3200-212 BMA Recessed-Mount Kits 24 in
 - 910-3200-212-I BMA Recessed-Mount Kits 600 mm

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

US & Canada

Tel: +1.801.975.7200

International

Tel: +1.801.975.7200

Sales

Tel: +1.801.975.7200
sales@clearone.com

Tech Support

Tel: +1.801.974.3760
audiotechsupport@clearone.com